

# **EU-Declaration of Performance** In accordance with Annex III of Regulation (EU) No.305/2011 and Commission Delegated Regulation (EU) No 574/2014

## No. 2884-CPR-00157\_EPS\_PU

**1.** Unique identification code of the product-type:

### HYGROSMART COVER OVER SYSTEM (EPS\_PU)

2. Intended use:

### External Thermal Insulation Composite Systems (ETICS) with renderings

3. Manufacturer:

ALCHIMICA SA 7, Lampsakou Str., 11528 Athens-Greece

**4.** Systems of AVCP:

System 2+

5. European Assessment Document:

EAD 040083-00-0404

European Technical Assessment:

ETA-20/0643 of 09-08-2021

Technical Assessment Body:

Technical and Test Institute for Construction Prague (1020)

Notified body:

**Business Quality Verification (2884)** 



#### 6. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire of thermal insulation material	E	
Water absorption	After 1h: 0.02 kg/m <sup>2</sup> After 24h: 0.25 kg/m <sup>2</sup> (Base coat) After 1h: 0.01 kg/m <sup>2</sup> After 24h: 0.1 kg/m <sup>2</sup>	EAD 040083-00- 0404
Hygrothermal behaviour	(Complete rendering) Resistant to hygrothermal cycles	
Freeze / thaw behaviour	Freeze / thaw resistant	
Bond Strength	Between the base coat and the thermal insulation product (mortar or paste): Initial state: $\geq 0.150$ MPa After hygrothermal cycles: $\geq 0.16$ MPa	
	Between the adhesive and the substrate: Initial state: ≥ 1.15 MPa Immersion 48h and 2h drying: ≥1.09MPa Immersion 48h and 7d drying: ≥1.26MPa	-
	Between the adhesive and the thermal insulation product: Initial state: ≥ 0.10MPa Immersion 48h and 2h drying: ≥ 0.05MPa Immersion 48h and 7d drying: ≥ 0.09MPa	
Thermal resistance	≥ 1.00 [(m2*K)/W]	1

**7.** Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Krimizis Christos CEO

Athens 14/04/2022